



One



Abbattitore Surgelatore da appoggio / *Top mounted blast chiller & freezer*

Abbattitore rapido di temperatura e surgelatore di piccola capacità per bar e utilizzi limitati.

- Cicli: Abbattimento rapido e Surgelazione a temperatura (con sonda al cuore) o a tempo.
- Controllo elettronico di facile utilizzo
- Modelli con o senza sonda al cuore
- Costruzione in acciaio inox AISI 304 interno ed esterno.
- Vano interno ed accessori facilmente pulibili grazie agli angoli arrotondati ed agli accessori completamente smontabili
- Gas refrigerante R 404 a
- Alimentazione: 230V/1Ph/50Hz

Small blast chiller & freezer for bars and pubs.

- *Cycles: Time and temperature (by using the core probe) blast chilling and blast freezing cycles;*
- *Control panel easy to use;*
- *Provided with or without core probe*
- *Stainless steel AISI 304 inside and outside;*
- *Easy clearing due to the internal rounded corners and the knock down trays supports;*
- *Refrigerant: R 404 a*
- *Power supply: 230V/1Ph/50Hz*



Controllo elettronico
Control panel



Sonda al cuore (mod. S)
Core probe (mod.S)



Costruzione in acciaio inox AISI 304
Stainless steel AISI 304

N° No.	Modello Model	Codice Code	Capacità KG in abbattimento positivo (+90°C / +3°C) <i>Blast chilling KG capacity (+90°C/+3°C)</i>	Capacità KG in surgelazione (+90°C / -18°C) <i>Blast freezing KG capacity (+90°C/-18°C)</i>	Sonda al cuore <i>Core probe</i>	Dimensioni (mm) <i>Dimensions (mm)</i>	Teglie GN / EN passo 70mm <i>GN pans / EN trays - 70mm pitch</i>	Alimentazione <i>Power Supply</i>	Dimensioni imballaggio (mm) <i>Packing dimensions (mm)</i>	Peso Netto/Lordo (Kg) <i>Net/Gross weight (Kg)</i>
1	ONE	9ABB01C11S001	7	5	no	600x607x371	3 GN2/3	230V/1Ph/50Hz	620x620x540	48/58
2	ONE-S	9ABB01C11S002	7	5	si/yes	600x607x371	3 GN2/3	230V/1Ph/50Hz	620x620x540	48/58